

### AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (currently amended) A method for allocating MCU ports ~~resources~~ for a multipoint network event, said method comprising ~~the steps of~~:

receiving an allocation request for the multipoint network event, said request at least associated with a number for the maximum MCU ports ~~resources~~ for the multipoint network event; and

determining the number of MCU ports ~~resources~~ to allocate at the start of the multipoint network event, the start MCU ports ~~resources~~ allocation number less than or equal in value to ~~than~~ the maximum MCU ports ~~resources~~ number.

2. (original) The method of claim 1 wherein the step of receiving the allocation request originates in the plurality of MCUs.

3. (original) The method of claim 1 wherein the step of receiving the allocation request originates in a common channel signaling interface.

4. (original) The method of claim 1 wherein the step of receiving the allocation request originates as an external allocation request.

5. (currently amended) The method of claim 1 wherein the step of determining comprises the step of calculating:

$$R = [(R_{MAX})(R_{SP})]_{R_{SM}}$$

where:  $R$  = said Number of Ports ~~Resources~~ to start

$R_{MAX}$  = Maximum Ports ~~Resources~~

$R_{SP}$  = Configurable Start Ports ~~Resource~~ Percentage

$R_{SM}$  = Configurable Minimum Start Ports ~~Resources~~

6. (currently amended) A method for time varying allocation of MCU ports resources during a multipoint network event, said method comprising the steps of:

determining the number of MCU ports resources to allocate for the start of the multipoint network event; and

at each of a plurality of modeling intervals during the multipoint network event, adjusting the number of allocated MCU ports resources based on users actually in the multipoint network event.

7. (currently amended) The method of claim 6 wherein the step of determining comprises the step of calculating:

$$R = [(R_{MAX})(R_{SP})]_{R_{SM}}$$

where:  $R$  = said Number of Ports Resources to start

$R_{MAX}$  = Maximum Ports Resources

$R_{SP}$  = Configurable Start Port Resource Percentage

$R_{SM}$  = Configurable Minimum Start Ports Resources

8. (currently amended) The method of claim 6 [[7]] wherein the step of adjusting comprises the step of calculating:

$$R_j = \left[ \sum_{events} \left( (R_{actual} + \frac{P_j}{1-S}) | R_{MAX} \right) \right] \left| \left( \sum_{events} R_{actual} \right) + 1 \right|$$

Where:

$R_j$  = Number of Ports Resources at a modeling interval  $j$  of said plurality modeling intervals

$R_{actual}$  = Number of Ports Resources actually used

$R_{MAX}$  = Maximum Ports Resources

$events$  = Number of multipoint network events

$P_j$  = Probability Value at each of said plurality of modeling intervals  $j$

$S$  = Confidence Factor

9. (currently amended) A method for allocating resources for a multipoint network event, said method comprising ~~the steps of~~:

obtaining available MCU capacity in a plurality of MCUs,

receiving an allocation request from an allocation requestor for the multipoint network event,

determining based on the received allocation request whether the multipoint network event can be started, if the multipoint network event can be started, the number of resources to allocate to start the multipoint network event, and, if the multipoint network event cannot be started, then informing the allocation requestor that the multipoint network event cannot be started,

allocating the number of resources to at least one MCU,

debiting the allocated resources from the available MCU capacity,

directing inbound users to the at least one MCU for participation in the multipoint network event.

10. (original) The method of claim 9 wherein the step of determining comprises the step of calculating:

$$R = [(R_{MAX})(R_{SP})]_{R_{SM}}$$

where:  $R$  = said Number of Resources to start

$R_{MAX}$  = Maximum Resources

$R_{SP}$  = Configurable Start Resource Percentage

$R_{SM}$  = Configurable Minimum Start Resources

11. (original) The method of claim 9 wherein the step of receiving the allocation request originates in the plurality of MCU's.

12. (original) The method of claim 9 wherein the step of receiving the allocation request originates in a common channel signaling interface.

13. (original) The method of claim 9 wherein the step of receiving the allocation request originates as an external allocation request.

14. (original) The method of claim 9 further comprising the step of:  
at each of a plurality of modeling intervals, adjusting the number of resources based on the number of inbound users actually in the multipoint network event.

15. (original) The method of claim 14 wherein the step of adjusting comprises the step of calculating:

$$R_j = \left[ \sum_{events} \left( (R_{actual} + \frac{P_j}{1-S}) | R_{MAX} \right) \right] \left| \left( \sum_{events} R_{actual} \right)^{-1} \right|$$

Where:

$R_j$  = Number of Resources at a modeling interval  $j$  of said plurality modeling intervals

$R_{actual}$  = Number of Resources actually used

$R_{MAX}$  = Maximum Resources

$events$  = Number of multipoint network events

$P_j$  = Probability Value at each of said plurality of modeling intervals  $j$

$S$  = Confidence Factor

16. (original) The method of claim 15 wherein the step of adjusting adjusts the number of resources at each modeling interval ( $f$ ) based on a configurable value for  $S$ .

17. (original) The method of claim 15 wherein the step of adjusting adjusts the number of resources at each modeling interval ( $f$ ) is based on a self-tuning value for  $P_j$ .

18. (original) The method of claim 17 wherein the self-tuning value for  $P_j$  comprises the step of calculating:

$$P_j = \frac{\sum_{i=1}^m (w_i)(\bar{R}_{i,j})}{\sum_{i=1}^m w_i}$$

Where:  $\bar{R}_{i,j} = \frac{R_j}{\sum_{j=1}^n R_j}$  = normalized resource accumulation

$w_i$  = the counted number of events at tuning interval  $i$

$R_j$  = the number of resources that have become utilized during modeling interval  $j$

$n$  = the number of modeling intervals ( $j$ ) in use

$m$  = the number of tuning intervals ( $i$ ) in use

19. (currently amended) A method for allocating MCU ports resources for a plurality of multipoint network events, said method comprising ~~the steps of~~:

- obtaining available MCU capacity in a plurality of MCUs,
- receiving allocation requests from ~~an~~ allocation requestors for the plurality of multipoint network events,
- determining based on each of said plurality of received allocation requests, the number of ports resources to allocate to start each of the ~~aforesaid~~ multipoint network events,
- allocating the number of ports resources to at least one MCU of said plurality of MCUs for each of the ~~aforesaid~~ multipoint network events,
- at each of a plurality of modeling intervals during each multipoint network event, adjusting the number of ports resources based on inbound users actually in the multipoint network event.

20. (original) A method for tuning the allocation of MCU resources for multipoint network events, said method comprising ~~the steps of~~:

- counting the number of multipoint network events that have been accumulated within at least one predetermined tuning interval,
- normalizing MCU resources actually utilized during each multipoint network event in each of the at least one predetermined tuning interval,
- determining a probability value for future use of MCU resources for an upcoming multipoint network event based on the steps of counting and normalizing.

21. (original) The method of claim 20 wherein the step of normalizing accumulates the number of resources at predetermined modeling intervals during each multipoint event.

22. (original) The method of claim 20 wherein the predetermined tuning interval is at least three orders of magnitude in time greater than the predetermined modeling interval.

23. (original) The method of claim 22 wherein the tuning interval is at least a day and the modeling interval is at least a minute.

09/812,971

**APPENDIX A – CLEAN LISTING OF CLAIMS**

1. (currently amended) A method for allocating MCU ports for a multipoint network event, said method comprising:

receiving an allocation request for the multipoint network event, said request at least associated with a number for the maximum MCU ports for the multipoint network event; and

determining the number of MCU ports to allocate at the start of the multipoint network event, the start MCU ports allocation number less than or equal in value to the maximum MCU ports number.

2. (original) The method of claim 1 wherein the step of receiving the allocation request originates in the plurality of MCUs.

3. (original) The method of claim 1 wherein the step of receiving the allocation request originates in a common channel signaling interface.

4. (original) The method of claim 1 wherein the step of receiving the allocation request originates as an external allocation request.

5. (currently amended) The method of claim 1 wherein the step of determining comprises the step of calculating:

$$R = [(R_{MAX})(R_{SP})]_{R_{SM}}$$

where:  $R$  = said Number of Ports to start

$R_{MAX}$  = Maximum Ports

$R_{SP}$  = Configurable Start Ports Percentage

$R_{SM}$  = Configurable Minimum Start Ports

6. (currently amended) A method for time varying allocation of MCU ports during a multipoint network event, said method comprising:

determining the number of MCU ports to allocate for the start of the multipoint network event; and

at each of a plurality of modeling intervals during the multipoint network event, adjusting the number of allocated MCU ports based on users actually in the multipoint network event.

7. (currently amended) The method of claim 6 wherein the step of determining comprises the step of calculating:

$$R = [(R_{MAX})(R_{SP})]_{R_{SM}}$$

where:  $R$  = said Number of Ports to start  
 $R_{MAX}$  = Maximum Ports  
 $R_{SP}$  = Configurable Start Port Percentage  
 $R_{SM}$  = Configurable Minimum Start Ports

8. (currently amended) The method of claim 6, wherein the step of adjusting comprises the step of calculating:

$$R_j = \left[ \sum_{events} \left( (R_{actual} + \frac{P_j}{1-S}) R_{MAX} \right) \right] \left( \sum_{events} R_{actual} \right) + 1$$

Where:

$R_j$  = Number of Ports at a modeling interval  $j$  of said plurality modeling intervals

$R_{actual}$  = Number of Ports actually used

$R_{MAX}$  = Maximum Ports

$events$  = Number of multipoint network events

$P_j$  = Probability Value at each of said plurality of modeling intervals  $j$

$S$  = Confidence Factor

9. (currently amended) A method for allocating resources for a multipoint network event, said method comprising:

obtaining available MCU capacity in a plurality of MCUs,



receiving an allocation request from an allocation requestor for the multipoint network event,

determining based on the received allocation request whether the multipoint network event can be started, if the multipoint network event can be started, the number of resources to allocate to start the multipoint network event, and, if the multipoint network event cannot be started, then informing the allocation requestor that the multipoint network event cannot be started,

allocating the number of resources to at least one MCU,

debiting the allocated resources from the available MCU capacity,

directing inbound users to the at least one MCU for participation in the multipoint network event.

10. (original) The method of claim 9 wherein the step of determining comprises the step of calculating:

$$R = [(R_{MAX})(R_{SP})]_{R_{SM}}$$

where:  $R$  = said Number of Resources to start

$R_{MAX}$  = Maximum Resources

$R_{SP}$  = Configurable Start Resource Percentage

$R_{SM}$  = Configurable Minimum Start Resources

11. (original) The method of claim 9 wherein the step of receiving the allocation request originates in the plurality of MCU's.

12. (original) The method of claim 9 wherein the step of receiving the allocation request originates in a common channel signaling interface.

13. (original) The method of claim 9 wherein the step of receiving the allocation request originates as an external allocation request.

14. (original) The method of claim 9 further comprising the step of:

at each of a plurality of modeling intervals, adjusting the number of resources based on the number of inbound users actually in the multipoint network event.

15. (original) The method of claim 14 wherein the step of adjusting comprises the step of calculating:

$$R_j = \left[ \sum_{events} \left( (R_{actual} + \frac{P_j}{1-S}) R_{MAX} \right) \right] \left( \sum_{events} R_{actual} \right)^{1-S}$$

Where:

$R_j$  = Number of Resources at a modeling interval  $j$  of said plurality modeling intervals

$R_{actual}$  = Number of Resources actually used

$R_{MAX}$  = Maximum Resources

$events$  = Number of multipoint network events

$P_j$  = Probability Value at each of said plurality of modeling intervals  $j$

$S$  = Confidence Factor

16. (original) The method of claim 15 wherein the step of adjusting adjusts the number of resources at each modeling interval ( $j$ ) based on a configurable value for  $S$ .

17. (original) The method of claim 15 wherein the step of adjusting adjusts the number of resources at each modeling interval ( $j$ ) is based on a self-tuning value for  $P_j$ .

18. (original) The method of claim 17 wherein the self-tuning value for  $P_j$  comprises the step of calculating:

$$P_j = \frac{\sum_{i=1}^n (w_i)(\bar{R}_{i,j})}{\sum_{i=1}^n w_i}$$

Where:  $\bar{R}_{i,j} = \frac{R_j}{\sum_{j=1}^n R_j}$  = normalized resource accumulation

$w_i$  = the counted number of events at tuning interval  $i$

$R_j$  = the number of resources that have become utilized during modeling interval  $j$

$n$  = the number of modeling intervals ( $j$ ) in use

$m$  = the number of tuning intervals ( $i$ ) in use

19. (currently amended) A method for allocating MCU ports for a plurality of multipoint network events, said method comprising:

obtaining available MCU capacity in a plurality of MCUs,

receiving allocation requests from allocation requestors for the plurality of multipoint network events,

determining based on each of said plurality of received allocation requests, the number of ports to allocate to start each of the multipoint network events,

allocating the number of ports to at least one MCU of said plurality of MCUs for each of the multipoint network events,

at each of a plurality of modeling intervals during each multipoint network event, adjusting the number of ports based on inbound users actually in the multipoint network event.

20. (currently amended) A method for tuning the allocation of MCU resources for multipoint network events, said method comprising:

counting the number of multipoint network events that have been accumulated within at least one predetermined tuning interval,

normalizing MCU resources actually utilized during each multipoint network event in each of the at least one predetermined tuning interval,

determining a probability value for future use of MCU resources for an upcoming multipoint network event based on the steps of counting and normalizing.

21. (original) The method of claim 20 wherein the step of normalizing accumulates the number of resources at predetermined modeling intervals during each multipoint event.

22. (original) The method of claim 20 wherein the predetermined tuning interval is at least three orders of magnitude in time greater than the predetermined modeling interval.

23. (original) The method of claim 22 wherein the tuning interval is at least a day and the modeling interval is at least a minute.